



Dinam LED Limited, Dynamic lighting for colorful life

PRODUCTS SPECIFICATION

LED Down Lamp

(Concise Series L Type)

LD-DLCL



Dinam LED Limited

Web: www.dinamled.com

Email: info@dinamled.com

Contact: Luisa

Tel: +86-755-23063529

Fax: +86-755-22700020

Mobile: +86-13600151478

Mobile: +86-13560459594

Address: B Building, Chuangfu Industrial Zone, Beihuan Road,
Shiyan Town, Baoan District, Shenzhen, China.

Introduction

The Concise -L series Down Lamp, adopt the die casting aluminum coating body, COB direct lighting source, with anti-glare cover ,there are several kinds choices for the angle luminous , good heat dissipation design minimized Lumens depreciation, external LED driver.



Features:

- ★ Tarning fast, no flickering ,and little glare. Immediately getting full flash output once lighted.
Applicable to frequent switch and various of combination lighting
- ★ No fluourent flicking, no Hg and lead contamination.
- ★ Operating temperature: -20~50°C.
- ★ Long life span LED lights, more than 50,000 hours +.
- ★ Water-proof, IP20.

Photos:



Products Size



Punch: $\varnothing 89^{+3}_{-0}$ mm

LD-DLCL

Main Parameter (T=20°C)

NUMBER	ITEM	LD-DLCL
01	Size	Ø120*97mm
02	Rated power	18W
03	LED type	COB 18W
04	Color	Warm white White
05	Luminous flux	2150lm (Warm white) 2200 lm(white)
06	Color temperature	2500~4000k(Warm white) 4000~7500k(White)
07	Life time	≥50,000 Hour
08	Operating temperature	-20°C to + 60°C
09	Storage temperature	-30°C to + 80°C
10	Certificates	CE .RoHS
11	Input voltage	100~240V
12	Punch	Punch: $\varnothing 89^{+3}_{-0}$ mm
13	Water proof	IP20
14	Beam Angle	12°/60°

Part number	Color	Current	Power	Luminous Flux
LD-DLCL-W	White	600mA	18 W	2200 lm
LD-DLCL-WW	Warm white	600mA	18 W	2150 lm

How to connect the power

Below shows you how to connect the down lamp to power supplies.

